



# ISOSTATIC BEARING SALES COMPANT



7.48 Inch | 190 Millimeter x 12.598 Inch | 320  
Millimeter x 5.039 Inch | 128 Millimeter SKF 24138  
CCK30/C2LW33VG004 Spherical Roller Bearings

Bearing No. 24138 CCK30/C2LW33VG004

24138 CCK30/C2LW33VG004 Bearing 2D drawings  
and 3D CAD models

Category	Spherical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	43.24
EAN	7316577650535
Product Group	B04311
Internal Clearance	C2-Snug
Mounting Method	Adapter Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Tapered
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	AH24138 (Specify bore)
Withdrawal Nut	KM40
Inch - Metric	Metric
Long Description	190MM Tapered Bore; 320MM Outside Diameter; 128MM Width; C2-Snug Clearance; Adapter Mount; Double Row of Spherical Roller Bearings; Steel Cage Material; Open Enclosure; Relubricatable
Other Features	Order adapter or



## ISOSTATIC BEARING SALES COMPANT

	withdrawal sleeve or nut separately. Others may be available
Category	Spherical Roller Bearing
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Weight / LBS	95.24
B	5.039 Inch   128 Millimeter
d	7.48 Inch   190 Millimeter
D	12.598 Inch   320 Millimeter
bore diameter:	190 mm
maximum rpm:	1500 RPM
outside diameter:	320 mm
operating temperature range:	Maximum of +390 ° F
overall width:	128 mm
cage material:	Steel
bore type:	Tapered 1:30
bearing material:	Steel
outer ring type:	Not Split
cage type:	Inner Ring Guided
internal clearance:	C2
precision rating:	Not Rated
closure type:	Open
finish/coating:	Uncoated
lubrication hole type:	Lubrication Groove & Hole
outer ring width:	128 mm
dynamic load capacity:	1600 kN
fillet radius:	2.5 mm
static load capacity:	2500 kN



# ISOSTATIC BEARING SALES COMPANT

series:

241