



ISOSTATIC BEARING SALES COMPANT



16.535 Inch | 420 Millimeter x 29.921 Inch | 760
 Millimeter x 10.709 Inch | 272 Millimeter SKF
 23284 CAK/C4W33 Spherical Roller Bearings

Bearing No. 23284 CAK/C4W33

23284 CAK/C4W33 Bearing 2D drawings and 3D CAD models

Category	Spherical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	565.41
EAN	7316577651068
Product Group	B04311
Internal Clearance	C4-Extra Loose
Mounting Method	Adapter Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Tapered
Cage Material	Bronze
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	AH3284 (Specify bore)
Withdrawal Nut	HM3188
Inch - Metric	Metric
Long Description	420MM Tapered Bore; 760MM Outside Diameter; 272MM Width; C4-Extra Loose Clearance; Adapter Mount; Double Row of Spherical Roller Bearings; Bronze Cage Material; Open Enclosure; Relubricatable; Adapter



ISOSTATIC BEARING SALES COMPANT

Other Features	Order adapter or withdrawal sleeve or nut separately. Others may be available
Category	Spherical Roller Bearing
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Manufacturer URL	http://www.skf.com
Weight / LBS	1,245.39
B	10.709 Inch 272 Millimeter
Adapter Part Number	SNP3284 (Specify bore) Inch H3284 (Specify bore) Millimeter
d	16.535 Inch 420 Millimeter
D	29.921 Inch 760 Millimeter
bore diameter:	420 mm
maximum rpm:	630 RPM
outside diameter:	760 mm
operating temperature range:	Maximum of +390 ° F
overall width:	272 mm
cage material:	Brass
bore type:	Tapered 1:12
bearing material:	Steel
outer ring type:	Not Split
cage type:	Inner Ring Guided
internal clearance:	C4
precision rating:	Not Rated
closure type:	Open
finish/coating:	Uncoated
lubrication hole type:	Lubrication Groove & Hole
outer ring width:	272 mm



ISOSTATIC BEARING SALES COMPANT

dynamic load capacity:	7350 kN
fillet radius:	6 mm
static load capacity:	11600 kN
series:	232