



ISOSTATIC BEARING SALES COMPANT

SHS35LC[1,2,3,4,5,6,7,8,9]+[
165-3000/1]L THK Linear Guide Standard
Accuracy and Preload Selectable SHS Series

Bearing No.
SHS35LC[1,2,3,4,5,6,7,8,9]+[165-3000/1]L

SHS35LC[1,2,3,4,5,6,7,8,9]+[165-3
000/1]L Bearing 2D drawings and 3D CAD models

Days to Ship	3 Days
Block Type	[Wide Long] LC: Long Flanged w/Tapped and Thru Holes
The number of LM blocks combined with a axis	1 ~ 9
Nominal Part Number	35
Rail Width W1	34 mm
Mounting Height M	48 mm
Rail Length L	165 ~ 3000 mm
Radial Clearance	Normal
Accuracy Grade	Normal Grade (Best Leadtime)
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	72900
Basic Load Rating Static Rating Co(N)	127000
Allowable Static Moment MA(N m)	2340
Allowable Static Moment MB(N m)	2340
Allowable Static Moment MC(N m)	2010
Block external dimension W	100 mm



ISOSTATIC BEARING SALES COMPANT

Block external dimension L	152 mm
Mounting hole for blocks	Tapped and Thru Holes
Mounting Hole Dimension S(M)	M10
Mounting Hole Dimension H(\varnothing)	8.5
Mounting Hole Screw Depth	Through mm
Block dimension L1	123 mm