



ISOSTATIC BEARING SALES COMPANT

HSR20CB[1,2,3,4,5,6,7,8,9]M
+[87-1480/1]LM THK Standard Linear Guide
Accuracy and Preload Selectable HSR Series

Bearing No.
HSR20CB[1,2,3,4,5,6,7,8,9]M+[87-1480/1]LM

HSR20CB[1,2,3,4,5,6,7,8,9]M+[87-
1480/1]LM Bearing 2D drawings and 3D CAD models

Days to Ship	22 Days
Block Type	[Wide] CB: Flanged w/Thru Holes and Middle Holes
The number of LM blocks combined with a axis	1 ~ 9
Nominal Part Number	20
Rail Width W1	20 mm
Material	Stainless Steel
Mounting Height M	30 mm
Rail Length L	87 ~ 1480 mm
Radial Clearance	Normal
Accuracy Grade	Normal Grade (Best Leadtime)
Retainer	N/A
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	19800
Basic Load Rating Static Rating Co(N)	27400
Allowable Static Moment MA(N m)	218
Allowable Static Moment MB(N m)	218
Allowable Static Moment MC(N m)	235



ISOSTATIC BEARING SALES COMPANT

Block Mounting Hole Pitch (Width Direction)	53 mm
Block Mounting Hole Pitch (Length Direction)	40 mm
Block Mounting Hole Diameter	6
Rail Mounting Hole Pitch	60 mm
Rail Mounting Hole Diameter	6
Symbols for Dust Resistance	None (Not Recommended)
Block external dimension W	63 mm
Block external dimension L	74 mm
Mounting hole for blocks	Thru Holes
Number of Block Mounting Holes(holes)	6
Mounting Hole Dimension H(\varnothing)	6
Mounting Hole Screw Depth	Through mm
Block dimension L1	50.8 mm