



ISOSTATIC BEARING SALES COMPANT

SHW35CAN[1,2,3,4,5,6,7,8,9]
]+[108-3000/1]L[H,P,SP,UP] THK Linear
 Guide Caged Ball Wide Rail SHW Accuracy and
 Preload Selectable

Bearing No.
 SHW35CAN[1,2,3,4,5,6,7,8,9]+[108-3000/1]L[H
 ,P,SP,UP]

SHW35CAN[1,2,3,4,5,6,7,8,9]+[10
 8-3000/1]L[H,P,SP,UP] Bearing 2D drawings
 and 3D CAD models

Days to Ship	3 Days
Block Type	[Wide] CA: Flanged w/Tapped Holes and Middle Holes
The number of LM blocks combined with a axis	1 ~ 9
Nominal Part Number	35
Rail Width W1	69 mm
Mounting Height M	35 mm
Material	Carbon Steel
Rail Length L	108 ~ 3000 mm
Radial Clearance	Normal
Accuracy Grade	High Grade / Precision Grade / Super Precision Grade / Extra High Precision Grade
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	35500
Basic Load Rating Static Rating Co(N)	49200
Allowable Static Moment MA(N m)	603
Allowable Static Moment MB(N m)	603



ISOSTATIC BEARING SALES COMPANT

Allowable Static Moment MC(N m)	1630
Grease Nipple Option	With Grease Nipple (Best Leadtime)
Block external dimension W	120 mm
Block external dimension L	107 mm
Number of Block Mounting Holes(holes)	6
Mounting Hole Dimension S(M)	M8
Mounting Hole Screw Depth	Through mm
Block dimension L1	83 mm