



ISOSTATIC BEARING SALES COMPANT

SR25W[1,2,3,4,5,6,7,8,9]C[0,1]+[96-3000/1]LY THK Radial Load Linear Guide Accuracy and Preload Selectable SR Series

Bearing No.
SR25W[1,2,3,4,5,6,7,8,9]C[0,1]+[96-3000/1]LY

SR25W[1,2,3,4,5,6,7,8,9]C[0,1]+[96-3000/1]LY Bearing 2D drawings and 3D CAD models

Days to Ship	5 Days
Block Type	[Standard] W: Standard
The number of LM blocks combined with a axis	1 ~ 9
Nominal Part Number	25
Rail Width W1	23 mm
Material	Carbon Steel
Mounting Height M	33 mm
Rail Length L	96 ~ 3000 mm
Radial Clearance	Light Preload / Medium Preload
Accuracy Grade	Normal Grade (Best Leadtime)
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	20300
Basic Load Rating Static Rating Co(N)	39500
Allowable Static Moment MA(N m)	286
Allowable Static Moment MB(N m)	175
Allowable Static Moment MC(N m)	355
Block external dimension	48 mm



ISOSTATIC BEARING SALES COMPANT

W	
Block external dimension L	83 mm
Mounting hole for blocks	Tapped Holes
Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M6
Mounting Hole Screw Depth	9 mm
Block dimension L1	59 mm