



ISOSTATIC BEARING SALES COMPANT

9CSR25+[116-3000/1]/[116-3000/1]L[P,SP,UP] THK Cross-Rail Guide Block Set

Bearing No. 9CSR25+[116-3000/1]/[116-3000/1]L[P,SP,UP]

9CSR25+[116-3000/1]/[116-3000/1]L[P,SP,UP]
Bearing 2D drawings and 3D CAD models

Days to Ship	82 Days
Rail Width W1	23 mm
Mounting Height M	70 mm
Number of blocks	9
Rail Length L	116 ~ 3000 mm
Radial Clearance	Normal
Accuracy Grade	Precision Grade / High Precision Grade / Extra High Precision Grade
Callout Size	25
Length of Y axis Rail (Only Applies To The Cross-guide)	116 ~ 3000
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	27200
Basic Load Rating Static Rating Co(N)	45900
The outside dimension W of block	78.6 mm
The outside dimension L of block	102.2 mm
The number of mounting hole for blocks(piece)	2 × 5
Mounting Hole Dimension S(M)	M6
Mounting Hole Screw Depth	10 mm



ISOSTATIC BEARING SALES COMPANT

Allowable static moment $M_o(N \cdot m)$	459
---------------------------------------------	-----