



ISOSTATIC BEARING SALES COMPANT

SHS65C1SS(GK) THK Caged Ball Linear Guide (Block Only) Standard Grade Interchangeable SHS Series

Bearing No. SHS65C1SS(GK)

Days to Ship	Same Day
RoHS	10
Block Type	[Wide] C: Flanged w/Tapped and Thru Holes
Nominal Part Number	65
Mounting Height M	90 mm
Material	Carbon Steel
Radial Clearance	Normal
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	205000
Basic Load Rating Static Rating Co(N)	320000
Allowable Static Moment MA(N m)	8260
Allowable Static Moment MB(N m)	8260
Allowable Static Moment MC(N m)	9400
Symbols for Dust Resistance	SS: End, Side, and Inner Seal (Standard seal - best leadtime)
Block external dimension W	170 mm
Block external dimension L	221 mm
Mounting hole for blocks	Tapped and Thru Holes
Mounting Hole Dimension S(M)	M16

SHS65C1SS(GK) Bearing 2D drawings and 3D CAD
models



ISOSTATIC BEARING SALES COMPANT

Mounting Hole Dimension H(\varnothing)	14.5
Mounting Hole Screw Depth	Through mm
Block dimension L1	175 mm
Enclosed Grease	AFB-LF