



ISOSTATIC BEARING SALES COMPANT

HSR35LB1UU(GK) THK Linear Guide (Block Only) Standard Grade Interchangeable HSR Series

Bearing No. HSR35LB1UU(GK)

Days to Ship	4 Days
RoHS	10
Block Type	[Wide Long] LB: Long Flanged w/Thru Holes (Obsolete)
Nominal Part Number	35
Rail Type	Standard
Mounting Height M	48 mm
Material	Carbon Steel
Radial Clearance	Normal
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	65000
Basic Load Rating Static Rating Co(N)	91700
Allowable Static Moment MA(N m)	1490
Allowable Static Moment MB(N m)	1490
Allowable Static Moment MC(N m)	1370
Block Mounting Hole Pitch (Width Direction)	82 mm
Block Mounting Hole Pitch (Length Direction)	62 mm
Block Mounting Hole Diameter	9
Rail Mounting Hole Pitch	80 mm

HSR35LB1UU(GK) Bearing 2D drawings and 3D CAD models



ISOSTATIC BEARING SALES COMPANT

Rail Mounting Hole Diameter	9
Symbols for Dust Resistance	UU: End seal
Block external dimension W	100 mm
Block external dimension L	134.8 mm
Mounting hole for blocks	Thru Holes
Mounting Hole Dimension H(\varnothing)	9
Mounting Hole Screw Depth	Through mm
Block dimension L1	105.8 mm